




TA-1414-E WIEGAND EMULATING KEYPAD



FEATURES

- Standard Wiegand Output
- Polymer Construction
- Built-In Sonalert
- Indoor/Outdoor use
- Up to 500 Feet from Control Panel
- Bi-Color Status LED




TA-1414-E Keypad Readers are field programmable as standard 26 bit or 37 bit proprietary Wiegand output for use on TAC's complete line of access control systems. Standard 26 Bit format can be used for connecting to other access control systems.

Model	Description
TA-1414-E	Wall Mount - Programmable Wiegand Output

A Bi-Colour LED and Sonalert provide users with both visual and audible signals of "Access Granted" or "Access Denied" conditions.

Specifications	TA-1414-E
Bi-Color LED	standard
Sonalert	standard
Operating Temp.	-40°C to 70°C (-40°F to 158°F)
Environment	Indoor/Outdoor
Supply Voltage	12VDC
Supply Current	30mA max.
Back Box	single gang electrical box
Cable Requirements	22 AWG, 6 conductor, overall shield, standard

Typical Door Configuration:



360 Carlingview Dr.
 Toronto, Ontario
 Canada, M9W 5X9
 Tel: (416) 798-0611
 Fax: (416) 798-1349
 www.kmthomas.com

Distributed by: